WI-710 Weighing Indicator

Features

- Up to 1 / 15000 resolution
- Attractive outline design with durable ABS housing
- Bright and clear Red LED display
- Adjustable filtering level for weighing under various conditions
- Zero / Tare / Weighing / Simple Counting / Net & Gross Weight/ **Check-Weighing function**
- Adjustable capacities, resolutions and parameters
- Supports up to eight 350 ohm analog load cell
- Auto shut off function for power saving
- Low battery indication with unique charging lamp
- Easy to operate and stable with modular software and hardware
- Using with floor scale, almost eliminating external large screen
- Ideal for applications in Production, Packaging, Warehouse, Inventory, Shipping and Receiving areas, especially in harsh and dark environment
- Optional RS-232+RTC+Relay Interface for Printer or Tower Light or PLC application
- Optional Plug & Play U-Key (Wire) / (Bluetooth) device for Weighing Data Transfer to PC (Without Any Driver)





Bluetooth U-Key

Wired USB U-Key

Specifications

Model	JWI-710
Resolution	1/15000
Weighing Unit	t, Ib, kg, pcs, 斤
Display	6 digits, 54 mm digit height, Red LED display
Dimension(mm)	274×170×117
Power supply	AC 100V~240V or Rechargeable battery (6V/4A)
Power consumption	Level 1 (least of bright) : power flow about 36mA, use time about 110 hours Level 2 (medium of bright) : power flow about 51mA, use time about 80 hours Level 3 (most of bright) : power flow about 61mA, use time about 65 hours
Certification	CE

Sizedraft









LED backlit

Load Cell



Jadever Scale Co., Ltd. Tel: 886-2-22990203 Fax: 886-2-22990204 http://www.jadever.com E-mail:sales@jadever.com.tw Xiamen Jadever Scale Co., Ltd. Tel: 86-592-6037668 Fax: 86-592-6037028 http://www.jadever.com E-mail:xmjadever@jadever.com.cn

Jadever Weightech, Inc. Tel:1-905-482-2618 Fax:1-905-887-4066 http://www.jadeverscale.com E-mail:james@jadeverscale.com