

SNUGIII Precision Balance

Features

- High Resolution in 1/30,000d, 1/60,000d & 1/120,000d
- Wind Shield device for a better weighing result
- Overload and transport devices
- Zero / Tare / Weighing / Piece Count / Sampling / Percentage Weighing / RTC / Check Weighing functions
- RS-232 Interface as a standard
- Ideal for applications including laboratory, jewelry, gold, silver, herbs, quality control, industrial, educational needs or any other use.
- Optional Plug & Play U-Key(Bluetooth) device for Weighing Data Transfer to PC or Android Tablets (Without Any Driver)

Temperature: 0°C~40°C
Humidity: 80%



AD:CS5530

MCU: 32 bit




HBM load cell for SNUG III-1200



Specifications

Model	SNUGIII -150	SNUGIII -300	SNUGIII -600	SNUGIII -1200	SNUGIII -1500	SNUGIII -3000
Capacity(g)	150	300	600	1200	1500	3000
Division-1(g)	0.005/0.002	0.01/0.005	0.02/0.01 0.005	0.05/0.02 0.01	0.05/0.02 0.01	0.1/0.05
Weighing units	13 weighing units: g, kg, ct, pound, ounce, troy ounces, grain, penny-weight Momme, Hong Kong tael, Singapore tael, Taiwan tael, tical tola					
Display	6 digits , 14mm digit height, LCD display with green LED back light					
Weighing pan (mm)	146×125 (stainless steel) as standard; Φ125 for high resolution					
Dimension(mm)	220X180X182 Eight cases in one box					
Weight	Net weight 1.15kg; Gross weight 1.85kg					
Power supply	4 C size dry batteries or adaptor					
Certification	CE					

Sizedraft



JADEVER[®]



Jadever Scale Co., Ltd.
Tel : 886-2-22990203
Fax : 886-2-22990204
http : www.jadever.com
E-mail:sales@jadever.com.tw

Xiamen Jadever Scale Co., Ltd.
Tel : 86-592-6037668
Fax : 86-592-6037028
http://www.jadever.com
E-mail:xmjadever@jadever.com.cn

Jadever Weigtech, Inc.
Tel:1-905-482-2618
Fax:1-905-887-4066
http://www.jadeverscale.com
E-mail:james@jadeverscale.com