

## JIK-6CSB-7611-4050-SS Platform Scale

### Features

- ❖ 304 Stainless Steel Setup
- ❖ OIML – Legal-For-Trade Purpose (1/ 3,000d)
- ❖ Stainless Steel Precision Loadcell
- ❖ Weighing Units : kg, g, lb,lb.oz
- ❖ Platform Base can setup either vertically or horizontally
- ❖ Simple Part Counting : pcs
- ❖ Adjustable non-slip rubber leveling feet
- ❖ Operating Environment : -10°C ~ 40°C ≤ 85% R.H.
- ❖ Optional Interface : Bluetooth 4.0 (Ukey),RS-232 (PC), Relay (External Tower Light / PLC), WIFI, or Label Printer



**WEIGHTS  
AND MEASURES  
OFFICE**  
Legal for Trade Purpose

**JIK-6CSB**



**Stainless Platform structure  
and Loadcell**

| Model                    | JIK-4CSB-7611-4050-SS-60K                                              | JIK-4CSB-7611-4050-SS-150K | JIK-4CSB-7611-4050-SS-300K |
|--------------------------|------------------------------------------------------------------------|----------------------------|----------------------------|
| Capacity                 | 60kg                                                                   | 150kg                      | 300kg                      |
| Readability (LFT)        | 0.02kg                                                                 | 0.05kg                     | 0.1kg                      |
| Stabilisation Time (sec) | 2                                                                      |                            |                            |
| Displayed Resolution     | 1/ 3,000d (LFT - Legal-For-Trade)                                      |                            |                            |
| Pan Size                 | 400mm x 500mm or 500mm x 400mm (stainless steel)                       |                            |                            |
| Base Structure           | 304 Stainless Steel                                                    |                            |                            |
| Weighing Units           | kg, g, lb,oz, pcs,                                                     |                            |                            |
| Calibration              | External Calibration                                                   |                            |                            |
| Display                  | Green Backlit LCD with 46mm Digits Height                              |                            |                            |
| Power Supply             | DC 9V, 0.4A (AC Adaptor Included) / SLA Re-Chargeable Battery (6V/4Ah) |                            |                            |
| Operating Temperature    | -10° to 40°C                                                           |                            |                            |
| Housing (Indicator)      | 304 Stainless Steel                                                    |                            |                            |
| Column Height            | 660-700mm ( Up-Down Angle Adjustable Indicator Bracket)                |                            |                            |
| Interface (optional)     | Ukey (Bluetooth), RS-232, WIFI                                         |                            |                            |